

ACER CO. LATHE Parameter (large)

Parameters	Delta B type	Functions and Settings
02-01	01	
02-00	01	Source of First Master Frequency Command, 0 to +10V from AVI
01-09	3	Accel Time 1, 0.01 to 3600.0 sec
01-10	4	Decel Time 1, 0.01 to 3600.0 sec
01-00	77.3 (Hz) 73.5	Maximum Output Frequency (Fmax), 50.00 to 400.00 Hz
01-07	100 (%) 73.5	Output Frequency Upper Limit, 1 to 120%
01-02	230	Maximum Output Voltage (Vmax), 230V series: 0.1V to 255.0V
01-01	60	Maximum Voltage Frequency (Fbase) 0.10 to 400.00 Hz
00-09	3	
11-00	0	
05-00	8.7	
01-14	8.7	
04-04	29	
04-05	35	
04-06	7	
04-02	101	AVI Input Gain, 1 to 200 %
04-17	101	AUI Input Gain, 01 to 200 %
11-06	8.6	
11-07	8.7	
02-03	3	
06-00	00	
07-00	95	Motor Rated Current, 30 to 120%
07-01	35	Motor No-Load Current, 01 to 90%
07-04	4	Number of Motor Poles, 02 to 10
01-11	3	
01-12	4	
01-16	02	
01-17	02	
00-07	11705	Password Input, 00 to 65535
00-08	11705	Password Set, 00 to 65535