

ACER Group

Springwood Industrial, Inc.
1062 N. Kraemer Place
Anaheim, CA 92806
Tel: 714-632-9701 Fax: 714-632-9730
<http://www.aceronline.net>
info@aceronline.net

Klim Industrial, Inc.
244 N. Randolphville Road
Piscataway, NJ 08854
Tel: 732-752-9100 Fax: 732-752-9101
<http://www.aceronline.net>
acer_klim@yahoo.com

The parameter for YASKAWA 616G5(220V class 3HP) WITHOUT braking resistor.

Accel Time	C1-01=8.0Sec
Decel Time	C1-02=7.0Sec
Fast Stop Time	C1-09=7.0Sec
Input Voltage	E1-04=230Vac
Max Frequency	E1-04=160Hz
Max Voltage	E1-05=230Vac
Mid Voltage	E1-08=12.6 Vac
Mm Voltage	E1-10=2.3Vac
Base Voltage	E1-13=230Vac
Motor Rated FLA	E2-01=9.00A
Motor Rated Slip	E2-02=0.71Hz
No-load Current	E2-03=5.17A
Term Resistance	E2-05=1 .084
Saturation Comp1	E2-07=0.44
Saturation Comp2	E2-08=0.68
Local/Remote Key	O2-01=Disable

To check constant that have been change from the factory setting are set, Go to MENU ->Modified Constants, the parameter is for ACER EVS mill only.